

BC-400 Low Speed Centrifuge



Features

1. Widely used in laboratory, hospital and etc..
2. Maintenance -free brushless motor, no powder pollution, quick in speed up and down.
3. Max. 5000rpm, smooth in operation, low noise and small vibration.
4. Micro computer control system, LCD display the RCF, time and speed.
5. Automatically store all the running parameters, which can be used directly next time when the machine is turned on.
5. Electric cover lock, compact design, super speed and imbalance protection.
6. With over speed and imbalance protection

BC-400 Technical Parameter:

Max. Speed	5000rpm
Max. RCF	2637×g
Max. Capacity	4×50ml
Time Range	0~99min
RPM/RCF Convert	Yes
Noise (dB)	≤ 55
Temperature	Normal
Acc/Dec	10 Kinds
Speed Accuracy	± 20r/min
Temperature Accuracy	/
Voltage(V/Hz)	AC 220V/110V 50HZ/60HZ
Size (W x D x Hmm)	280×220×175mm
Net Weight(Kg)	3.5KG
Certificates	CE,ISO & Calibration report are available

Matched Rotors for BC-400

Order No.	Rotor Type	Max Speed (rpm)	Max Volume (ml)	Max RCF (g)
NO31501	Angle Rotor	5000	4x50ml	2615
NO31502	Angle Rotor	5000	6x15/10ml	2637
			6x7ml vacuum tube adapter	2637
			6x5ml vacuum tube adapter	2637